

HG 2200 R

*“Sober, robust and ideal for
continuous monitor analyzers”*



UHP Hydrogen Generator



MODEL

HG 2200 R

FEATURES

- Purity better than 99,999%*
- Outlet pressure: 1 - 4 barg** defined simply by the keyboard
- Removable and external water tank included
- Continuous water loading pump available

* max O2 content 0,1 ppm when used with additional purifier

** Standard setting 4 barg, manually adjustable by the operator. 6 barg available on demand

APPLICATIONS

Dedicated for THC and fumes Monitor Analyzers



TECHNICAL SPECIFICATIONS

FLOW RATE	200 Nml/min
POWER RATING	100 VA
NOISE LEVEL	< 46 dB
ELECTRICAL SUPPLY	115 - 230 Vac 50 - 60 Hz available on the same item
OPERATING TEMPERATURE	between 5°C and 40°C
H2O SUPPLY	Demineralised H2O $\leq 5 \mu\text{S}/\text{cm}^2$ (0,2 M Ω) @ 20 °C
CONSUMABLES	dryer with molecular sieve
DIMENSIONS	Height: 31 cm Width: 48cm Depth: 38 cm
WEIGHT	20 kg
WARRANTY	1 year

CERTIFICATIONS



Complies with **ATEX**





CLAIND

GAS GENERATORS AND PURIFIERS

Via Regina 24
22016 Tremezzina
Loc. Lenno (CO)
Italy

Ph. +39 0344 56603
Fax +39 0344 56627
Email: info@claind.it
Website: www.claind.it